

# County Surveyor's Record, Douglas County, Oregon

16673

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

34.05 Creek, 6 lks. wide, course S. 5° W.; asc. 75 ft. over SE. slope.

36.39 Point for the 80 1/16 sec. cor. of sec. 23 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/16 S 23 80  
1981

from which

A fir, 7 ins. diam., bears S. 68° E., 33 lks. dist., mkd. 80 1/16 S23 BT.

A cedar, 10 ins. diam., bears S. 50 1/2° W., 10 1/2 lks. dist., mkd. 80 1/16 S23 BT.

Ascend 90 ft. over SE. slope.

43.00 Spur, slopes S. 10° W.; desc. 5 ft. over SW. slope.

43.52 The cor. of secs. 14, 15, 22, and 23.

Land, mountainous.

Soil, rocky clay.

Timber, cedar, yew, oak, chinquapin, fir, hemlock, maple, madrone, pine, and ash; undergrowth, salal, poison oak, fern, Oregon grape, vine maple, hazel, arrowwood, wild rose, blackberry, huckleberry, thimbleberry, salmonberry, willow, and young timber.

From the cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by Floyd W. Cole, Deputy County Surveyor, in 1923, recorded by Arthur Boyer, Registered Engineer No. 1581, in 1957, and recorded by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1980, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 29 S R 7 W  
3|2  
10|11  
1957

from which the remains of the original bearing trees

A white oak, 29 ins. diam., bears N. 15° E., 62 lks. dist., with healed blaze.

A root hole, bears S. 25° W., 105 lks. dist., with a down oak alongside, size indeterminate, no marks visible.

A white oak, 40 ins. diam., bears N. 45° W., 50 lks. dist., with healed blaze.

and a bearing tree mkd. by Cole

A white oak, 10 ins. diam., bears S. 50° E., 18 lks. dist., with healed blaze. (Record, 16 lks.)

and a new bearing tree

A fir, 15 ins. diam., bears S. 45° W., 50 lks. dist., mkd. T29S R7W S10 BT.