

County Surveyor's Record, Douglas County, Oregon

16674

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

From this point, a fence corner bears S. 45° W., 0.04 chs. dist., fences extending S. and E.

N. 8° 49' E., bet. secs. 2 and 3.

Ascend 85 ft. over broken SW. slope, through heavy timber and dense undergrowth.

5.65 Spur, slopes S. 75° W.; desc. 15 ft. over NW. slope.

8.05 Ravine, drains S. 75° W.; asc. 225 ft. over SW. slope.

15.60 Ridge, bears N. 50° E. and S. 85° W.; desc. 100 ft. over NW. slope.

19.99 The S 1/16 sec. cor. of secs. 2 and 3, established by Glenn S. Baughman, Registered Land Surveyor, No. 536, in 1980, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Baughman:

A fir, 8 ins. diam., bears N. 40° E., 20 lks. dist., with scribe marks S 1/16 S2 BT visible on open blaze.

A fir, 12 ins. diam., bears S. 45 1/2° W., 35 1/2 lks. dist., with scribe marks S 1/16 S 3 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 3/S 2
1981

Reset iron rod alongside iron post.

N. 8° 49' E., beginning new measurement.

Descend 150 ft. over NW. slope.

7.25 Ravine, drains S. 80° W.; asc. 150 ft. over SW. slope.

12.80 Dirt road, 20 lks. wide, bears N. 20° W. and S. 60° E.

15.80 Dirt road, 20 lks. wide, bears N. 15° E. and S. 10° W.

17.50 Ridge, bears N. 5° E. and S. 15° W.; desc. 60 ft. over NE. slope.

19.25 Gravelled road, 25 lks. wide, bears N. 40° W. and S. 30° E.

19.99 The 1/4 sec. cor. of secs. 2 and 3, reestablished by proportionate measurement and recorded by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1980, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.