

# County Surveyor's Record, Douglas County, Oregon

16675

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

T 29 S R 7 W  
1/4 |  
S 3 | S 2  
1980  
RLS 536

from which bearing trees mkd. by Baughman

A madrone, 31 ins. diam., bears S. 59 1/2° E., 93 lks. dist., with scribe marks 1/4 S2 BT visible on open blaze.

A fir, 11 ins. diam., bears N. 34 3/4° W., 44 lks. dist., with scribe marks 1/4 S3 BT visible on open blaze.

From this point, United States Coast and Geodetic Survey triangulation station "TWO OAKS 1942", bears S. 86° 28' E. 117.27 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a standard brass cap, 3 1/2 ins. diam., mkd. TWO OAKS 1942, and a triangle.

\_\_\_\_\_

N. 8° 47' E., beginning new measurement.

Descend 150 ft. over NE. slope.

- 4.35 Ravine, drains E.; asc. 90 ft. over broken SE. slope.
- 11.25 Spur, slopes S. 50° E.; desc. 125 ft. over broken NE. slope.
- 20.00 Point for the N 1/16 sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16  
S 3 | S 2  
1981

from which

A fir, 6 ins. diam., bears N. 58° E., 29 lks. dist., mkd. N 1/16 S2 BT.

A fir, 6 ins. diam., bears S. 46 1/2° W., 52 lks. dist., mkd. N 1/16 S3 BT.

From this point, the corner of fences, bears N. 45° E., 0.055 chs. dist., with fences extending N. and W., and downed fences extending S. and E.

Descend 370 ft. over NE. slope, along old woven wire fence.

- 32.40 McNabb Creek, 15 lks. wide, course N. 35° W.; asc. 60 ft. over SW. slope.
- 40.14 The cor. of secs. 2, 3, 34, and 35.

Land, mountainous.  
Soil, rocky clay.  
Timber, ash, willow, alder, madrone, oak, fir, cedar, hemlock, yew, pine, and chinquapin, undergrowth, fern,