

County Surveyor's Record, Douglas County, Oregon

16676

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>Oregon grape, poison oak, hazel, arrowwood, blackberry, thimbleberry, huckleberry, salal, wild rose, manzanita, and young timber.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89° 28' W., bet. secs. 3 and 10.</p> <p>Descend 270 ft. over broken SW. slope, through heavy timber and dense undergrowth.</p>
16.95	<p>Creek, 10 lks. wide, course N. 60° W.; asc. 10 ft. over NE. slope.</p>
18.73	<p>Point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> $E \frac{1}{16} \frac{S \ 3}{S \ 10}$ <p>1981</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 36 1/4° W., 30 lks. dist., mkd. E 1/16 S3 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 34 1/4° E., 38 1/2 lks. dist., mkd. E 1/16 S10 BT.</p> <p>Ascend 20 ft. over NE. slope.</p>
20.05	<p>Spur, slopes N. 10° E.; asc. 40 ft. over NE. slope.</p>
21.85	<p>Ravine, drains N. 50° E.; asc. 450 ft. over broken SE. slope.</p>
37.46	<p>The 1/4 sec. cor. of secs. 3 and 10, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, further recorded by Glenn S. Baughman, Registered Land Surveyor, in 1980, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 29 S R 7 W</p> $\frac{1}{4} \frac{S \ 3}{S \ 10}$ <p>1962</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">An oak snag, 22 ins. diam., bears N. 23° W., 15 lks. dist., with illegible scribe marks visible on opened blaze, remarked by Byron, with scribe marks 1/4 S3 CS BT visible on open blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 39 1/2° E., 54 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 39 1/2° W., 58 lks. dist., mkd. 1/4 S3 BT.</p>