

County Surveyor's Record, Douglas County, Oregon

16680

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A madrone, 28 ins. diam., bears S. 80° W., 48 lks. dist., with scribe marks 29S R7W S33 CS BT visible on open blaze. This tree was rescribed by James W. Byron, Deputy County Surveyor, in 1962.

and the remains of bearing trees mkd. by Mensch

A fir snag, 12 ins. diam., bears N. 29° E., 14 lks. dist., with healed blaze. (Record, N. 24° E.)

A cedar, 20 ins. diam., bears N. 70° W., 41 lks. dist., with healed blaze. (Record, N. 68 1/4° W.)

and a new bearing tree

A fir, 8 ins. diam., bears N. 41° E., 40 lks. dist., mkd. T29S R7W S27 BT.

N. 88° 55' W., bet. secs. 28 and 33.

Descend 85 ft. over NW. slope, through heavy timber and dense undergrowth.

7.80 Ravine, drains N. 15° W.; asc. 200 ft. over broken NE. slope.

19.40 The E 1/16 sec. cor. of secs. 28 and 33, established and recorded by Victor McLind, Registered Land Surveyor No. 934, in 1972, and is accepted as the corner, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 29 S R 7 W
E 1/16 $\frac{S\ 28}{S\ 33}$
RLS 934
1972

from which bearing trees mkd. by McLind

A cedar, 10 ins. diam., bears N. 77 1/4° E., 28 1/2 lks. dist., with scribe marks E 1/16 S28 BT visible on open blaze.

A cedar, 10 ins. diam., bears S. 41° W., 21 1/2 lks. dist., with scribe marks E 1/16 S33 BT visible on open blaze.

Corner is located at top of ascent, slopes N.

N. 88° 55' W., beginning new measurement.

Descend 355 ft. over general W. slope.

18.50 Dirt road, 15 lks. wide, bears N. and S.

19.40 The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

1/4 $\frac{S\ 28}{S\ 33}$
1924

from which the remains of bearing trees mkd. by Mensch