County Surveyor's Record, Douglas County, Oregon

16683

Subdivision of Section 3, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	C N 1/16 | S 3 C 1981
	from which
	A fir, 12 ins. diam., bears N. 65 1/4° E., 82 lks. dist., mkd. CN 1/16 S3 BT.
	A fir, 20 ins. diam., bears S. 89 1/2° W., 137 lks. dist., mkd. CN 1/16 S3 BT.
	Descend 60 ft. over NW. slope.
65.50	Woven wire fence, extends N. 75° W., and S 75° E.
66.85	Creek, 3 lks. wide, course N. 70° W.; asc. 65 ft. over SW. slope.
74.40	Spur, slopes N. 30° E.; desc. 75 ft. over NW. slope.
80.35	Woven wire fence, extends N. 85° W. and S. 85° E.
82.25	The 1/4 sec. cor. of secs. 3 and 34
	From the 1/4 sec. cor. of secs. 2 and 3.
	N. 87° 22' W., on the E. and W. center line of sec. 3.
	Ascend 30 ft. over NE. slope, through heavy timber and dense undergrowth.
0.60	Gravelled road, 20 lks. wide, bears NW. and SE.
1.65	Spur, slopes NW.; desc. 155 ft. over NW. slope.
2.50	Gravelled road, 20 lks. wide, bears N. 30° W. and S. 5° E., in curve.
6.85	Head of ravine, drains S. 50° W.; asc. 35 ft. over SE. slope.
8.25	Spur, slopes S. 30° W.; desc. 60 ft. over SW. slope.
10.70	Ravine, drains S. 15° W.; asc. 5 ft. over SE. slope.
12.50	Spur, slopes S. 10° W.; desc. 20 ft. over SW. slope.
15.00	Ravine, drains S. 35° E.; asc. 180 ft. over SE. slope.
19.04	Point for the center E 1/16 sec. cor. of sec. 3.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	C E 1/16 / S 3 C 1981
	from which
	A fir, 18 ins. diam., bears N. 15 1/2° E., 82 lks. dist., mkd. CE 1/16 S3 BT.