

County Surveyor's Record, Douglas County, Oregon

16684

Subdivision of Section 3, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A fir, 16 ins. diam., bears S. 32° W., 13 lks. dist., mkd. CE 1/16 S3 BT.</p> <p>Ascend 5 ft. over SE. slope.</p>
19.20	Spur, slopes S. 20° W.; desc. 135 ft. over SW. slope.
25.35	Head of ravine, drains S. 40° W.; desc. 30 ft. over SW. slope.
30.20	Spur, slopes S. 55° W.; desc. 230 ft. over SW. slope.
36.30	Head of ravine, drains S. 70° W.; desc. 50 ft. over SW. slope.
38.08	<p>The center 1/4 sec. cor. of sec. 3.</p> <p>Descend 150 ft. over broken SW. slope.</p>
45.55	Gravelled road, 20 lks. wide, bears N. 20° W. and S. 20° E.
46.50	Creek, 10 lks. wide, course N. 20° W.; asc. 85 ft. over broken NE slope.
53.05	Spur, slopes N. 15° E.; desc. 10 ft. over broken NW. slope.
55.25	<p>Point for the center W 1/16 sec. cor. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $C \frac{W \frac{1}{16}}{S \ 3} C$ <p>1981</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 25 3/4° W., 68 lks. dist., mkd. CW 1/16 S3 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 10 3/4° W., 65 lks. dist., mkd. CW 1/16 S3 BT.</p> <p>From this point, a corner established by Arthur Boyer, Registered Engineer No. 1581, in 1957, bears N. 77° 05' E., 0.286 chs. dist., monumented with a fir, 18 ins. diam., with healed blazes on N., S., E., and W., faces, from which a bearing tree mkd. by Boyer:</p> <p style="margin-left: 40px;">A cedar, 24 ins. diam., bears S. 86° W., 55 lks. dist., with healed blaze.</p> <p>Descend 105 ft. over broken NW. slope.</p>
72.42	The 1/4 sec. cor. of secs. 3 and 4.
	<p>From the center E 1/16 sec. cor. of sec. 3.</p> <p>N. 8° 11' E., on the N. and S. center line of the NE 1/4 of sec. 3.</p> <p>Ascend 15 ft. over SE. slope, through heavy timber and dense undergrowth.</p>