

County Surveyor's Record, Douglas County, Oregon

16685

Subdivision of Section 3, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
4.35	Spur, slopes S. 80° W.; desc. 380 ft. over NE. slope, changing to NW. slope.
14.75	Ravine, drains N. 70° W.; asc. 5 ft. over SW. slope.
15.40	Spur, slopes N. 70° W.; desc. 25 ft. over NW. slope.
16.70	Ravine, drains N. 80° W.; asc. 45 ft. over SW. slope.
19.15	Woven wire fence, extends E. and W.
19.91	Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the NE 1/4 of sec. 3. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap mkd. NE 1/16 S 3 1981 from which A fir, 8 ins. diam., bears N. 33° E., 66 1/2 lks. dist., mkd. NE. 1/16 S3 BT. A fir, 11 ins. diam., bears S. 63 1/2° E., 92 lks. dist., mkd. NE. 1/16 S3 BT. Ascend 5 ft. over SW. slope.
21.50	Spur, slopes N. 80° W.; desc. 260 ft. over NW. slope.
40.20	The E 1/16 sec. cor. of secs. 3 and 34.
From the N 1/16 sec. cor. of secs. 2 and 3. N. 87° 33' W., on the E. and W. center line of the NE 1/4 of sec. 3. Ascend 130 ft. over NE. slope, through heavy timber and dense undergrowth, along fence line.	
4.90	Spur, slopes N. 5° W.; desc. 270 ft. over NW. slope, changing to SW. slope.
19.27	The NE 1/16 sec. cor. of sec. 3. Descend 105 ft. over SW. slope.
25.05	Ravine, drains N. 40° W.; asc. 5 ft. over NE. slope.
28.15	Spur, slopes N. 10° E.; desc. 20 ft. over NW. slope.
30.15	Ravine, drains N. 15° E.; asc. 45 ft. over NE. slope.
32.15	Woven wire fence, extends N. 5° E. and S. 5° W.
33.40	Spur, slopes N. 10° W.; desc. 120 ft. over broken NW. slope.
38.52	The center N 1/16 sec. cor. of sec. 3.
From the E 1/16 sec. cor. of secs. 3 and 10.	