

County Surveyor's Record, Douglas County, Oregon

16686

Subdivision of Section 3, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
	N. 8° 11' E., on the N. and S. center line of the SE 1/4 of sec. 3.
	Descend 30 ft. over NE. slope, through heavy timber and dense undergrowth.
3.75	Creek, 15 lks. wide, course N. 50° W.; asc. 50 ft. over SW. slope.
7.45	Spur, slopes S. 60° W.; desc. 90 ft. over NW. slope.
8.50	Ravine, drains S. 70° W.; asc. 215 ft. over SW. slope.
15.15	Spur, slopes N. 60° W.; desc. 160 ft. over NW. slope.
18.45	Gravelled road, 20 lks. wide, bears N. 70° E. and S. 75° W.
20.48	Point for the SE 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the SE 1/4 of sec. 3.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	SE 1/16 S 3 1981
	from which
	A fir, 6 ins. diam., bears N. 28 1/2° E., 130 lks. dist., mkd. SE 1/16 S3 BT.
	A fir, 4 ins. diam., bears S. 26 1/4° E., 61 lks. dist., mkd. X BT.
	Descend 25 ft. over NW. slope.
21.65	Creek, 5 lks. wide, course S. 65° W.; asc. 220 ft. over SW. slope.
29.10	Ravine, drains S. 25° E.; asc. 50 ft. over SE. slope.
32.30	Spur, slopes S. 70° E.; desc. 5 ft. over SE. slope.
34.35	Head of ravine, drains S. 35° E.; asc. 200 ft. over NE. slope.
40.96	The center E 1/16 sec. cor. of sec. 3.
	From the S 1/16 sec. cor. of secs. 2 and 3.
	N. 88° 56' W., on the E. and W. center line of the SE 1/4 of sec. 3.
	Descend 120 ft. over broken NW. slope, through heavy timber and dense undergrowth.
6.15	Spur, slopes N. 30° W.; desc. 195 ft. over NW. slope.
10.65	Ravine, drains N. 30° W.; desc. 160 ft. over NW. slope.
13.95	Gravelled road, 20 lks. wide, bears N. 65° E. and S. 70° W.