

# County Surveyor's Record, Douglas County, Oregon

**16687**

Subdivision of Section 3, T. 29 S., R. 7 W.,  
Willamette Meridian, Oregon

CHAINS	
18.89	The SE. 1/16 sec. cor. of sec. 3.  Descend 30 ft. over NW. slope.
21.35	Creek, 2 lks. wide, course S. 70° W.; desc. 30 ft. along broken S. slope.
28.95	Gravelled road, 20 lks. wide, bears N. 30° W. and S. 25° E.
30.65	Creek, 8 lks. wide, course N. 20° W.; asc. 200 ft. over NE. slope.
37.76	The center S 1/16 sec. cor. of sec. 3.
<p>From the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 4° 16' E., on the N. and S. center line of the SW 1/4 of sec. 3.</p> <p>Ascend 25 ft. over SW. slope, through heavy timber and dense undergrowth.</p>	
2.20	Spur, slopes N. 70° W.; desc. 60 ft. over NW. slope.
5.95	Ravine, drains N. 70° W.; asc. 90 ft. over SW. slope.
10.95	Spur, slopes S. 80° W.; desc. 150 ft. over NW. slope.
20.20	Ravine, drains S. 50° W., from N. 5° E.; asc. slightly over SW. slope, also fence, extends N. 70° E. and S. 70° W.
20.26	Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the SW 1/4 of sec. 3.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW 1/16 S 3 1981
	from which
	A fir, 18 ins. diam., bears N. 45° E., 96 lks. dist., mkd. SW 1/16 S3 BT.
	A pine, 13 ins. diam., bears S. 70 1/4° W., 218 lks. dist., mkd. SW. 1/16 S3 BT.
	Set a 6 ft. steel fence post alongside iron post.
	Ascend 40 ft. over SE. slope.
22.35	Ravine, drains S. 5° W.; asc. 85 ft. over SW. slope.
27.70	Spur, slopes E.; desc. 255 ft. over broken NW. slope.
28.95	Woven wire fence, extends N. 20° E. and S. 20° W.
29.35	Woven wire fence, extends N. 20° W. and S. 15° E.
40.52	The center W 1/16 sec. cor. of sec. 3.