

# County Surveyor's Record, Douglas County, Oregon

16688

Subdivision of Section 3, T. 29 S., R. 7 W.,  
Willamette Meridian, Oregon

CHAINS	
	<p>From the center S 1/16 sec. cor. of sec. 3.</p> <p>N. 84° 58' W., on the E. and W. center line of the SW 1/4 of sec. 3.</p> <p>Ascend 215 ft. over NE. slope, through heavy timber and dense undergrowth.</p>
6.45	Spur, slopes N. 40° W.; desc. 300 ft. over SW. slope.
15.85	Woven wire fence, extends N. 70° E. and S. 70° W.
15.90	Ravine, drains S. 50° W., from N. 5° E.; asc. over SE. slope.
15.94	<p>The SW 1/16 sec. cor. of sec. 3.</p> <p>Ascend 35 ft. over SE. slope.</p>
20.60	Spur, slopes S. 50° W.; desc. 205 ft. over SW. slope.
24.45	Woven wire fence, extends N. 30° W. and S. 30° E.
28.70	Dirt road, 15 lks. wide, bears N. 20° W. and S. 30° E.
29.05	Power line, bears N. 25° W. and S. 25° E.
30.85	Woven wire fence, bears N. 30° W. and S. 30° E.
30.90	Creek, 10 lks. wide, course N. 35° W.; asc. 5 ft. over NE. slope.
31.88	The S 1/16 sec. cor. of secs. 3 and 4.
<p>Subdivision of Section 23, T. 29 S., R. 7 W., Willamette Meridian, Oregon</p>	
	<p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 15' E., on the N. and S. center line of sec. 23.</p> <p>Ascend 150 ft. over broken SE. slope, through heavy timber and dense undergrowth.</p>
14.20	Spur, slopes S. 55° W.; desc. 10 ft. over NW. slope.
15.15	Creek, 2 lks. wide, course S. 55° W.; asc. 55 ft. over SW. slope.
16.75	Spur, slopes S. 30° W.; desc. 5 ft. over NW. slope.
17.20	Head of ravine, drains S. 70° W.; asc. 160 ft. over S. slope.
23.30	Spur, slopes N. 80° W.; desc. 255 ft. over NE. slope.
40.04	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>