

County Surveyor's Record, Douglas County, Oregon

16689

Subdivision of Section 23, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS

T 29 S R 7 W
C 1/4 S 23
1981

from which

A cedar, 13 ins. diam. bears N. 42 1/2° E., 66 lks.
dist., mkd. C 1/4 S23 BT.

A grand fir, 18 ins. diam., bears S. 44° E., 69
lks. dist., mkd. C 1/4 S23 BT.

Descend 20 ft. over NE. slope.

42.15 Ravine, drains N. 30° W.; desc. 160 ft. over NW. slope.

58.10 Spur, slopes N. 20° W.; desc. 40 ft. over NE. slope.

60.04 Point for the center N 1/16 sec. cor. of sec. 23.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with aluminum cap mkd.

C
N 1/16 | S 23
C
1981

from which

A fir, 8 ins. diam., bears S. 85 1/2° E., 12 lks.
dist., mkd. X BT.

A fir, 8 ins. diam., bears N. 33 1/2° W., 17 lks.
dist., mkd. CN 1/16 S23 BT.

Descend 275 ft. over NE. slope.

70.85 Byron Creek, 10 lks. wide, course N. 65° W.; asc. 140 ft.
over SW. slope.

81.84 The 1/4 sec. cor. of sec. 23 only.

From the 1/4 sec. cor. of secs. 23 and 24, perpetuated and
recorded by John M. Powell, Deputy County Surveyor, in
1969, monumented with an iron post, 1 1/4 ins. diam., firmly
set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 29 S R 7 W
1/4 S 23 | S 24
1969

from which the remains of the original bearing trees

A sawed fir stump, size indeterminate, bears
S. 52 1/2° E., 49 lks. dist., no mark visible.

A fir, 16 ins. diam., bears N. 26 1/2° W., 26 lks.
dist., with healed blaze.

and a new bearing tree

A fir, 9 ins. diam., bears S. 16° E., 43 1/2 lks.
dist., mkd. 1/4 S24 BT.