

County Surveyor's Record, Douglas County, Oregon

16690

Subdivision of Section 23, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS

S. 89° 49' W., on the E. and W. center line of sec. 23.

Descend 425 ft. over SW. slope, changing to NW. slope,
through heavy timber and dense undergrowth.

16.90 Creek, 5 lks. wide, course N. 25° E.; asc. 470 ft. over
SE. slope.

30.70 Spur, slopes N. 10° E.; desc. 160 ft. over NW. slope.

39.85 Ravine, drains N.; asc. 5 ft. over NE. slope.

39.94 The center 1/4 sec. cor. of sec. 23.

Ascend 25 ft. over NE. slope.

43.00 Spur, slopes N. 20° W.; desc. 60 ft. over NW. slope.

48.40 Head of ravine, drains N. 10° W.; asc. 25 ft. over NE.
slope.

50.80 Spur, slopes N. 30° W.; desc. 65 ft. over NW. slope.

55.60 Bottom of descent, drains N.; asc. 90 ft. over NE. slope.

59.97 Point for the center W 1/16 sec. cor. of sec. 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

$$\begin{array}{c} \text{C} \frac{\text{W } 1/16}{\text{S } 23} \text{C} \\ 1981 \end{array}$$

from which

A fir, 15 ins. diam., bears N. 68° W., 45 lks.
dist., mkd. CW 1/16 S23 BT.

A fir, 20 ins. diam., bears S. 89 1/2° W., 11 1/2 lks
dist., mkd. CW 1/16 S23 BT.

Ascend 60 ft. over NE. slope.

63.05 Spur, slopes N. 30° W.; desc. 155 ft. over NW. slope.

69.05 Head of ravine, drains N. 20° W.; asc. 70 ft. over NE.
slope.

74.25 Spur, slopes N. 15° W.; desc. 155 ft. over NW. slope.

80.00 Point for the center 80 1/16 sec. cor. of sec. 23.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{C} \frac{1/16}{\text{S } 23} 80 \\ 1981 \end{array}$$

from which

A cedar, 18 ins. diam., bears S. 89 1/2° E., 8 lks.
dist., mkd. C 80 1/16 S23 BT.

A fir, 9 ins. diam., bears N. 71° W., 30 lks.
dist., mkd. C 80 1/16 S23 BT.