

County Surveyor's Record, Douglas County, Oregon

16691

Subdivision of Section 23, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
	Ascend 5 ft. over NE. slope.
82.55	Spur, slopes N. 20° W.; desc. 135 ft. over NW. slope.
87.19	The 1/4 sec. cor. of sec. 23 only.
	From the center W 1/16 sec. cor. of sec. 23.
	N. 0° 20' E., on the N. and S. center line of the NW 1/4 of sec. 23.
	Descend 225 ft. over NE. slope, through scattering timber and dense undergrowth.
7.75	Ravine, drains NW.; desc. 125 ft. over broken NW. slope.
19.40	Creek, 1 lk. wide, course N. 50° W.; asc. 5 ft. over SW. slope.
20.00	Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the NW 1/4 of sec. 23.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	NW 1/16 S 23 1981
	from which
	A fir, 5 ins. diam., bears N. 56 1/2° E., 39 lks. dist., mkd. X BT.
	A fir, 10 ins. diam., bears S. 60° W., 22 1/2 lks. dist., mkd. NW 1/16 S23 BT.
	Ascend 5 ft. over SW. slope.
20.30	Spur, slopes N. 30° W.; desc. 95 ft. over NE. slope.
24.95	Creek, 2 lks. wide, course N. 45° W.; asc. 20 ft. over SW. slope.
31.25	Spur, slopes N. 45° W.; desc. 170 ft. over NE. slope.
38.35	Byron Creek, 10 lks. wide, course W.; asc. 40 ft. over S. slope.
41.86	The W 1/16 sec. cor of sec. 23 only.
	From the center 80 1/16 sec. cor. of sec. 23.
	N. 0° 24' E., on the N. and S. 80 1/16 line of the NW 1/4 of sec. 23.
	Descend 310 ft. over NW. slope, through heavy timber and dense undergrowth.
20.00	Point for the N 80 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the NW 1/4 of sec. 23. No permanent monument established.
	Descend 135 ft. over NW. slope.