

County Surveyor's Record, Douglas County, Oregon

16692

Subdivision of Section 23, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
36.50	Byron Creek, 10 lks. wide, course N. 80° W.; asc. 120 ft. over SE. slope.
41.86	The 80 1/16 sec. cor. of sec. 23 only.
	From the center N 1/16 sec. cor. of sec. 23.
	S. 89° 48' W., on the E. and W. center line of the NW 1/4 of sec. 23.
	Ascend 5 ft. over NE. slope, through heavy timber and dense undergrowth.
0.60	Spur, slopes N. 20° W.; desc. 75 ft. over NW. slope.
7.20	Creek, 3 lks. wide, course N. 5° W.; asc. 25 ft. over NE. slope.
12.40	Spur, slopes N. 30° W.; desc. 100 ft. over NW. slope.
17.25	Ravine, drains N. 20° E.; asc. 30 ft. over NE. slope.
19.45	Spur, slopes N. 40° W.; desc. 5 ft. over SW. slope
20.00	The NW 1/16 sec. cor. of sec. 23.
	Descend 25 ft. over SW. slope.
21.05	Creek, 1 lk. wide, course N. 70° W.; desc. 50 ft. over broken W. slope.
28.95	Ravine, drains NW.; asc. 5 ft. over NE. slope.
31.00	Top of ascent, slopes NW.; desc. 85 ft. over NW. slope.
40.01	Point for the N 80 1/16 sec. cor. of sec. 23.
	Descend 10 ft. over NW. slope.
44.35	Spur, slopes N. 20° W.; desc. 35 ft. over NW. slope.
47.17	The N 1/16 sec. cor. of sec. 23 only.
Subdivision of Section 33, T. 29 S., R 7 S., Willamette Meridian, Oregon	
From the 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.	
<u>1/4 S 33</u> 1924	
from which the remains of the original bearing trees	
A root hole, bears S. 10° W., 30 lks. dist., with a down madrone alongside, 20 ins. diam., with decayed blaze, no marks visible.	
A decayed madrone stump, 18 ins. diam., bears N. 17° W., 50 lks. dist., with axe marks visible on decayed blaze.	