

County Surveyor's Record, Douglas County, Oregon

16693

Subdivision of Section 33, T. 29 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
	and bearing trees mkd. by Mensch
	A fir, 15 ins. diam., bears N. 43° E., 23 lks. dist., with healed blaze.
	A fir, 10 ins. diam., bears N. 46° W., 18 lks. dist., with healed blaze. (Record, N. 49° W.)
	N. 4° 01' E., on the N. and S. center line of sec. 33.
	Ascend 15 ft. over SW. slope, through scattering timber and dense undergrowth.
1.90	Spur, slopes SW; desc. 180 ft. over NW. slope.
9.50	Ravine, drains W.; asc. 50 ft. over SW. slope.
11.80	Spur, slopes W.; desc. 20 ft. over broken NW. slope.
12.95	Bottom of descent, slopes W.; asc. 35 ft. over SW. slope.
18.30	Leave timber, enter old logged area, edge bears E. and W.
19.00	Spur, slopes W.; desc. 180 ft. over NW. slope.
27.38	Point for the center 1/4 sec. cor. of sec. 33, at inter- section with the E. and W. center line.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 S R 7 W C 1/4 S 33 1981
	from which
	A pine, 8 ins. diam., bears N. 23 1/2° E., 17 lks. dist., mkd. C 1/4 S33 BT.
	A pine, 5 ins. diam., bears N. 76° W., 22 lks. dist., mkd. X BT.
	Descend 25 ft. over NW. slope.
30.10	Ravine, drains N. 50° W.; asc. 25 ft. over SW. slope.
30.90	Spur, slopes W.; desc. 330 ft. over NW. slope.
52.40	Creek, 4 lks. wide, course NW.; asc. 55 ft. over SW. slope.
66.72	The 1/4 sec. cor. of sec. 28 and 33.
	From the 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	1/4 S 33 S 34 1924
	from which a bearing tree mkd. by Mensch
	A fir, 35 ins. diam., bears N. 81° W., 54 lks. dist., with healed blaze.