

# County Surveyor's Record, Douglas County, Oregon

16694

Subdivision of Section 33, T. 29 S., R. 7 W.,  
Willamette Meridian, Oregon

CHAINS	
	and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1962
	A fir, 15 ins. diam., bears S. 45° E., 17 lks. dist., with healed blaze.
	A fir, 15 ins. diam., bears S. 49 1/2° W., 16 lks. dist., with healed blaze.
	S. 89° 58' W., on the E. and W. center line of sec. 33.
	Descend 305 ft. over broken NW. slope, through scattering timber and dense undergrowth.
10.00	Ravine, drains NW.; asc. 45 ft. over broken NE. slope.
16.40	Spur, slopes NW.; desc. 140 ft. over SW. slope.
20.61	Point for the center E 1/16 sec. cor. of sec. 33.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{---} \text{S } 33 \text{---} \text{C} \\ 1981 \end{array}$
	from which
	A fir, 20 ins. diam., bears N. 16 1/2° E., 48 lks. dist., mkd. CE 1/16 S33 BT.
	A madrone, 13 ins. diam., bears S. 60 1/4° E., 87 1/2 lks. dist., mkd. CE 1/16 S33 BT.
	Descend 70 ft. over W. slope.
22.45	Dirt road, 25 lks. wide, bears N. and S.
23.55	Creek, 3 lks. wide, course N. 20° W.; asc. 70 ft. over NE. slope.
33.45	Spur, slopes NW.; desc. 140 ft. over NW. slope.
38.45	Ravine, drains NW.; asc. 5 ft. over NE. slope.
41.22	The center 1/4 sec. cor. of sec. 33.
	Descend 25 ft. over NW. slope.
47.50	Spur, slopes N. 60° W.; desc. 125 ft. over broken SW. slope.
54.45	Creek, 3 lks. wide, course N. 10° E.; asc. 50 ft. over E. slope.
55.95	Spur, slopes N.; desc. 35 ft. over broken NW. slope.
57.95	Creek, 1 lk. wide, course N.; desc. 5 ft. over NW. slope.
59.95	Creek, 2 lks. wide, course N. 60° E.; asc. 155 ft. over NE. slope.
68.20	Spur, slopes N. 35° E.; desc. 165 ft. over broken NW. slope.