

County Surveyor's Record, Douglas County, Oregon

16699

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A burned fir, 31 ins. diam., bears N. 55° E., 43 lks. dist., mkd. T20S R7W S31 BT.

Set a 5 ft. steel fence post alongside iron post.

(Rehabilitating a corner established by William P. Wright, in 1883, and remonumented by Thomas A. Tillman, in 1950)

The 1/4 Sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

1/4 S 36
1950

from which the remains of the original bearing trees.

A burned and dead fir, 55 ins. diam., bears S. 60° E., 38 lks. dist., no marks visible on burned blaze.

A burned and sawed fir stump, 70 ins. diam., bears West, 26 lks. dist., no marks visible on burned blaze.

and the remains of the bearing trees mkd. in 1950

A burned hemlock, 15 ins. diam., bears S. 37 1/4° W., 41 lks. dist., no marks visible on burned blaze. Rescribed 1/4 S36 BT on new blaze.

A burned and sawed fir stump, 11 ins. diam., bears N. 28° W., 127 lks. dist., with burned blaze. Rescribed 1/4 S36 BT on new blaze.

Set a 5 ft. steel fence post alongside iron post.

(Rehabilitating a corner established by William P. Wright, in 1883, and remonumented by Thomas A. Tillman, Raymond M. Bicknell, Hans W. Theilsen, and Joseph S. Gawron, in 1954.)

The cor. of secs. 13 and 24 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, and in a mound of stone, 1 ft. base, to top, with brass cap mkd.

T 20 S | T 20 S
S 13 | R 7 W
S 24 |
R 8 W | S 19
1954

from which the remains of the original bearing trees

A maple stump, 24 ins. diam., bears N. 70° E., 36 lks. dist., no marks remaining on burned blaze. (Record, N. 62° E., 39 lks.)

A burned firstump, 30 ins. diam., bears S. 65° W., 31 lks. dist., no marks remaining on burned blaze. (Record, S. 74° W.)