

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

16760

CHAINS

and the remains of the bearing tree marked in 1954

A decayed fir stump, 36 ins. diam., bears
N 41° W., 63 lks. dist., no marks remaining.
(Record, N. 38 3/4° W., 65 lks.)

from which a new bearing tree and a bearing object

A sawed fir stump, 33 ins. diam., bears
N. 27° W., 93 lks. dist. mkd. T20S R8W S13 BT.

A sandstone outcrop, 3 x 6 x 3 ft. above ground,
bears S. 19 1/2° W., 62 1/2 lks. dist., mkd. X on face.

(Rehabilitating a corner established by Thomas E. Todd,
in 1891, and remonumented by Thomas A. Tillman, Raymond
M. Bicknell, Hans W. Thielsen and Joseph S. Gawron.
in 1954)

The closing corner of secs. 18 and 19, on the W. bdy. of
T. 20 S., R. 7 W., monumented with an iron post, 2 ins.
diam., firmly set, projecting 3 ins. above ground with
brass cap mkd.

T 20 S	T 20 S
S 13	S 18 C
R 8 W	S 19 C
	R 7 W
	1954

from which the remains of the bearing trees mkd in 1954

A fir snag, 52 ins. diam., bears N. 58 1/2° E., 120
lks. dist., with burned blaze. Rescribed T20S
R7W S18 BT on new blaze.

A burned maple stump, size indeterminate, bears
S. 87° E., 84 lks. dist., no marks remaining on
burned blaze.

(Rehabilitating corners established by William P. Wright,
in 1883, and remonumented by Thomas A. Tillman, Raymond
M. Bicknell, Hans W. Thielsen and Joseph S. Gawron,
in 1954)

The 1/4 sec. cor. of sec. 13 only, monumented with an iron
post, 1 in. diam., firmly set, projecting 3 ins. above
ground, with brass cap mkd.

1/4 S 13	
	1954

from which the original bearing trees

A fir, 60 ins. diam., bears N. 12° E., 25 lks.
dist., no marks remaining on burned blaze.

A fir, 66 ins. diam., bears N. 73° W., 28 lks.
dist., no marks remaining on burned blaze.