

County Surveyor's Record, Douglas County, Oregon

16701

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree marked in 1954

A fir, 58 ins. diam., bears S. 89° W., 37 lks. dist., no marks remaining on burned blaze. Rescribed 1/4 S13 BT on new blaze.

The cor. of secs. 12 and 13 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 20 S	T 20 S
S 12	R 7 W
S 13	S 18
R 8 W	
	1954

from which the remains of the original bearing trees

A fir stump, 60 ins. diam., bears S. 80° E., 25 lks. dist., no marks remaining on burned blaze.

A burned and dead cedar, 60 ins. diam., bears N. 35° W., 16 lks. dist., no marks remaining on burned blaze. (Record, 12 lks.) Rescribed T20S R8W S12 BT on new blaze.

and the remains of the bearing tree marked in 1954

A root hole, bears S. 86 3/4° W., 89 lks. dist., with a down cedar stump alongside, 23 ins. diam., with scribe marks T20S R8W S13 BT visible on open blaze. (Record, 91 lks.)

The 1/4 sec. cor. of sec. 21 only, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4 S12	
	1954

from which the original bearing trees

A fir, 20 ins. diam., bears S. 65° E., 15 lks. dist., no marks remaining on decayed blaze.

A fir, 60 ins. diam., bears S. 52° W., 10 lks. dist., with healed blaze.

and a bearing tree marked in 1954

A fir, 50 ins. diam., bears N. 51 1/2° W., 70 lks. dist., with healed blaze. Rescribed 1/4 S12 BT on new blaze.

The cor. of Secs. 1 and 12 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 20 S	T 20 S
S 1	R 7 W
S 12	S 7
R 8 W	
	1954