

County Surveyor's Record, Douglas County, Oregon

16702

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the bearing trees marked in 1954

A burned fir, 58 ins. diam., bears S. 87 1/2° W.,
39 lks. dist., no marks remaining on burned
blaze. (Record, 37 lks.) Rescribed T20S
R8W S12 BT on new blaze.

A burned fir, 53 ins. diam., bears N. 36 1/2° W.,
68 lks. dist., no marks remaining on burned
blaze. (Record, 64 lks.) Rescribed T20S
R8W S1 BT on new blaze.

(Rehabilitating a corner reestablished by
Thomas A. Tillman, Raymond M. Bicknell,
Hans W. Thielsen, and Joseph S. Gawron, in 1954)

The 1/4 sec. cor. of sec. 1 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

1/4 S 1 |
1954

from which the remains of the bearing trees marked in 1954

A burned and dead fir, 15 ins. diam., bears
S. 51° W., 31 lks. dist., with healed blaze.
(Record, S. 47° W.)

A fir, 15 ins. diam., bears N. 19° W., 24 lks.
dist., with healed blaze.

and a tree of which I have no record

A burned and dead fir, 15 ins. diam., bears
N. 38 1/2° E., 19 lks. dist., with healed
blaze.

and new bearing trees

A fir, 12 ins. diam., bears S. 29° W.,
156 lks. dist., mkd. 1/4 S1 BT.

A fir, 18 ins. diam., bears N. 13° W.,
83 lks. dist., mkd. 1/4 S1 BT.

(Rehabilitating a corner established by
William P. Wright in 1883, and rehabilitated
by Charles M. Collier, in 1891, and
remonumented by Thomas A. Tillman, in 1949)

The cor. of Tps. 19 and 20 S., R. 8 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 19 S | T 20 S
R 8 W | R 7 W
S 36 | S 6
S 1 |
T 20 S |
1949