

County Surveyor's Record, Douglas County, Oregon

16704

Remonumentation of Certain Original Corner Points
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A burned fir, 60 ins. diam., bears
N. 63 3/4° W., 43 lks. dist., with healed
blaze.

A root hole, bears S. 64 1/2° W., 40 lks.
dist. with a down fir alongside, 23 ins.
diam., no marks remaining on burned blaze.

and a new bearing tree

A burned fir, 50 ins. diam., bears S. 34 1/2° W.,
102 lks. dist., mkd. 1/4 S1 BT.

Set a 6 ft. steel fencepost alongside the
iron post.

(Rehabilitating a corner established by
William P. Wright, in 1863, and
remonumented by Thomas A. Tillman, in 1950)

The cor. of secs. 1, 2, 35, and 36, monumented with an
iron post, 2 ins. diam., firmly set, projecting 10 ins.
above ground, with brass cap mkd.

T	20	S	R	8	W
	S	35		S	36
	S	2		S	1
	T 21 S				
	1950				

from which the remains of the original bearing trees

A burned fir stump, 20 ins. diam., bears
S. 41° W., 58 lks. dist., no marks remaining.

A fir snag, 35 ins. diam., bears N. 87° W.,
68 lks. dist., no marks remaining on burned
blaze.

and the remains of the bearing trees marked in 1950

A burned and dead fir, 32 ins. diam., bears
N. 60° E., 47 lks. dist., with healed blaze.

A burned and dead fir, 23 ins. diam., bears
S. 44 1/2° E., 22lks. dist. with healed blaze.

A burned and dead fir, 15 ins. diam., bears
S. 39° W., 18 lks. dist., with healed blaze.

A burned and dead fir, 16 ins. diam., bears
N. 34 1/4° W., 19 lks. dist. with healed blaze.

Set a 6 ft. steel fencepost alongside the
iron post.

(Rehabilitating a corner reestablished by
Thomas A. Tillman, in 1950)

The 1/4 sec. cor. of secs. 2 and 35, monumented with an
iron post, 1 in. diam., firmly set, projecting 10 ins.
above ground, with brass cap mkd.

1/4	S	35
	S	2
	1950	