

# County Surveyor's Record, Douglas County, Oregon

16705

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the bearing trees marked in 1950

A burned and dead hemlock, 15 ins. diam., bears N. 16° E., 41 lks. dist., with scribe marks 1/4 S35 BT visible on open blaze. (Record, fir)

A burned fir, 24 ins. diam., bears S. 83 1/2° W., 19 lks. dist. with healed blaze.

Set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating corners established by William P. Wright, in 1883, and remonumented by Thomas A. Tillman, in 1950)

The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

T	20	S	R	8	W
	S	34		S	35
	S	3		S	2
	T	21	S		
	1950				

from which the remains of the original bearing trees

A burned fir snag, 55 ins. diam., bears S. 35° E., 29 lks. dist., no marks remaining on bark blaze. Rescribed T21S R8W BT on new blaze.

A burned fir snag, 40 ins. diam., bears S. 34° W., 30 lks. dist., no marks remaining on bark blaze. (Record, S. 44° W., 26 lks.)

A burned and dead fir, 57 ins. diam., bears N. 88° W., 47 lks. dist., no marks remaining on bark blaze. Rescribed T20S R8W S34 BT on new blaze.

and the remains of the bearing trees marked in 1950

A hemlock, 16 ins. diam., bears N. 30° E., 39 lks. dist., no marks remaining on burned blaze.

A burned and dead fir, 60 ins. diam., bears S. 59 1/4° W., 59 lks. dist., with healed blaze.

and a new bearing tree

A burned and dead fir, 67 ins. diam., bears N. 52° E., 55 lks. dist., mkd. T20S R8W S35 BT.

Set a 6 ft. steel fencepost alongside the iron post.

The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.