

County Surveyor's Record, Douglas County, Oregon

16706

Remonumentation of Certain Original Corner Points
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

1/4 $\frac{S\ 34}{S\ 3}$
1950

from which the remains of the original bearing trees

A fir stub, 10 ins. diam., bears N. 18° E.,
8 lks. dist., no marks remaining on burned
blaze.

A burned and dead fir, 26 ins. diam., bears
S. 5° W., 20 lks. dist., with healed
blaze.

and the remains of the bearing tree marked in 1950

A burned and dead fir, 25 ins. diam., bears
N. 15° E., 16 lks. dist., with healed
blaze.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating corners established by
William P. Wright, in 1883, and remonumented
by Norman D. Price and George F. Rigby in 1945)

The cor. of secs. 3, 4, 33, and 34, monumented with an
iron post, 2 ins. diam., firmly set, projecting 14 ins.
above ground with brass cap mkd.

T 20 S R 8 W
 $\frac{S\ 33\ | S\ 34}{S\ 4\ | S\ 3}$
T 21 S
1945

from which the remains fo the original bearing trees

A burned fir snag, 15 ins. diam., bears
N. 27° E., 33lks. dist., with healed
blaze.

A burned fir, 32 ins. diam., bears
S. 44 3/4° E., 36 lks. dist., with healed
blaze.

A burned fir snag, 20 ins. diam., bears
S. 24 1/2° W., 25 lks. dist., with no marks
remaining on burned blaze.

and the remains of the bearing trees marked in 1945

A burned fir, 25 ins. diam., bears S. 70° W.,
43 lks. dist., with healed blaze.

A burned fir, 25 ins. diam., bears N. 61° W.,
60 lsk. dist. with healed blaze.

and a new bearing tree

A fir, 18 ins. diam., bears N. 11° E.,
48 lks. dist., mkd. T20S R8W S34 BT.

Set a 5 ft. steel fence post alongside the
iron post.