

County Surveyor's Record, Douglas County, Oregon

16707

Remonumentation of Certain Original Corner Points
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

1/4 $\frac{S\ 33}{S\ 4}$
1945

from which the remaining original bearing tree

An alder, 15 ins. diam., bears S. 37° W.,
24 lks. dist., no marks remaining on burned
blaze. (Record, S. 32° W.) Rescribed 1/4 S4
BT on new blaze.

And the remains of the bearing trees marked in 1945

A burned fir stump, 70 ins. diam., bears
N. 18 3/4° E., 55 lks. dist., with fragmentary
scribe marks visible on burned blaze.

and a new bearing tree

An alder, 6 ins. diam., bears N. 49 1/2° W.,
51 1/2 lks. dist., mkd. 1/4 S33 BT.

Set a 5 ft. steel fencepost alongside the
iron post.

The cor. of secs. 4, 5, 32, and 33, determined at record bearing and distance from the remains of the original bearing trees

A burned cedar stump, bears S. 75° E.,
43 lks. dist., no marks remaining.

A burned cedar stump, 8 ins. diam., bears
S. 62° W., 6 lks. dist., no marks remaining.

and the remains of the bearing trees marked in 1945

A burned fir stump, 56 ins. diam., bears
S. 61° E., 66 lks. dist., no scribe marks
remaining on burned blaze. Rescribed T20S
R8W S4 BT on new blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 20 S R 8 W
 $\frac{S\ 32\ | S\ 33}{S\ 5\ | S\ 4}$
T 21 S R 8 W
1967

from which new bearing trees

A cedar stump, 40 ins. diam., bears N. 1/4° E.,
111 lks. dist., mkd. T20S R8W S33 BT.

A burned cedar stump, 56 ins. diam., bears
N. 56° W., 174 lks. dist., mkd. T20S R8W
S32 BT.

The 1/4 sec. cor. of secs. 5 and 32, monumented with an