

County Surveyor's Record, Douglas County, Oregon

16708

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

1/4 $\frac{S\ 32}{S\ 5}$

1945

from which the remains of the original bearing trees

A burned fir, 30 ins. diam., bears
N. 19 1/4° E., 5 lks. dist., with healed blaze.

A burned fir snag, 16 ins. diam., bears
S. 13 1/2° E., 20 lks. dist., with healed blaze.

and the remains of the bearing tree marked in 1945

A burned fir, 30 ins. diam., bears S. 76° W.,
56 lks. dist., no marks visible on open
and burned blaze. Rescribed 1/4 S5 BT on
new blaze.

Set a 5 ft. steel fence post alongside the
iron post.

The cor. of secs. 5, 6, 31, and 32, monumented with an
iron post, 2 ins. diam., firmly set, projecting 5 ins.
above ground, with brass cap mkd.

T 20 S R 8 W
 $\frac{S\ 31\ | S\ 32}{S\ 6\ | S\ 5}$
T 21 S
1945

from which the remains of the bearing trees marked in
1945

A burned fir snag, 25 ins. diam., bears
N. 68 1/2° E., 23 1/2 lks. dist., with no marks
remaining on burned blaze. (Record,
N. 67° E., 21 lks.) Rescribed T20S R8W
S32 BT on new blaze.

A burned fir snag, 12 ins. diam., bears
S. 36 1/2° E., 128 lks. dist., no marks
remaining on burned blaze.

A burned fir snag, 27 ins. diam., bears
S. 10° W., 176 lks. dist., no marks
remaining on burned blaze.

and new bearing trees

A fir stump, 22 ins. diam., bears S. 11 1/2° E.,
67 lks. dist., mkd. T21S R8W S5 BT.

A burned fir snag, 25 ins. diam., bears
S. 22° W., 116 lks. dist., mkd. T21S R8W
S6 BT.

A burned fir snag, 17 ins. diam., bears
N. 17 1/2° W., 55 lks. dist., mkd. T 20S R8W
S31 BT.

Set a 5 ft. steel fence post alongside the iron
post.