

# County Surveyor's Record, Douglas County, Oregon

16710

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

The 1/4 sec. cor. of sec. 36 only, T. 20 S., R. 9 W., on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

1/4 S 36 |  
1954

from which bearing trees marked in 1954

An alder, 14 ins. diam., bears S. 46 1/2° W., 29 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

An alder, 20 ins. diam., bears N. 43° W., 17 lks. dist., with healed blaze. (Record, N. 39° W.)

Set a 5 ft. steel fence post alongside the iron post.

(Rehabilitating a corner reestablished by  
Thomas A. Tillman, in 1950)

The cor. of secs. 30 and 31 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 20 S | T 20 S  
R 9 W | S 30  
S 36 | S 31  
R 8 W  
1950

from which remains of the bearing trees marked in 1950

A burned fir, 23 ins. diam., bears N. 11 1/2° E., 33 lks. dist., no marks visible on open and burned blaze. Rescribed T20S R8W S30 BT on new blaze.

A fir, 23 ins. diam., bears S. 34 1/2° E., 34 lks. dist., with healed blaze.

and a local bearing tree

A fir, 25 ins. diam., bears N. 86 1/2° E., 43 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

(Rehabilitating a corner established by  
Thomas A. Tillman, and Joseph S. Gawron,  
in 1954)

The 1/4 sec. cor. of sec. 25 only, T. 20 S., R. 9 W., on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground with brass cap mkd.

1/4 S 25 |  
1954