

# County Surveyor's Record, Douglas County, Oregon

16711

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees marked in 1954

A fir, 28 ins. diam., bears S. 13° W.,  
10 lks. dist., with healed blaze.

A fir, 21 ins. diam., bears N. 85 3/4° W.,  
24 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron  
post.

(Rehabilitating a corner established by  
William P. Wright, in 1883, and remonumented  
by Thomas A. Tillman, in 1950)

The cor. of secs. 19 and 30 only, monumented with an iron  
post, 2 ins. diam., firmly set, projecting 12 ins. above  
ground, with brass cap mkd.

T 20 S	T 20 S
	S 19
R 9 W	S 30
S 25	R 8 W
1950	

from which bearing trees marked in 1950

A fir, 34 ins. diam., bears N. 47 1/2° E.,  
30 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 58° E.,  
25 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the  
iron post.

(Rehabilitating a corner reestablished by  
Thomas A. Tillman, and Joseph S. Gawron,  
in 1954)

The closing corner of secs. 24 and 25, only, T. 20 S.,  
R. 9 W., on the E. bdy. of the Tp., monumented with an  
iron post, 2 ins. diam., firmly set, projecting 8 ins.  
above ground, with brass cap mkd.

T 20 S	T 20 S
	S 19
CC	S 24
	S 25
R 9 W	R 8 W
1954	

from which the remains of the bearing trees marked in  
1954

A root hole, bears N. 25° W., 33 lks. dist.,  
with a down maple alongside, 18 ins. diam.,  
with fragmentary scribe marks visible on  
decayed blaze.

and new bearing trees

A maple, 25 ins. diam., bears S. 22° W.,  
153 lks. dist., mkd. T20S R9W S25 CC BT.

A maple, 39 ins. diam., bears N. 74° W.,