

County Surveyor's Record, Douglas County, Oregon

16713

Remonumentation of Certain Original Corner Points
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

(Rehabilitating a corner established by
William P. Wright, in 1883, and remonumented
by Thomas A. Tillman, Joseph S. Gawron,
Hans W. Thielsen, and Raymond M. Bicknell,
in 1954)

The cor. of secs. 18 and 19 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

| | |
|--------|--------|
| T 20 S | T 20 S |
| R 9 W | S 18 |
| | S 19 |
| S 24 | R 8 W |
| 1954 | |

from which the remains of the original bearing trees

A cedar, 60 ins. diam., bears N. 4° E.,
28 lks. dist., no marks remaining on burned
blaze.

A burned hemlock stump, 18 ins. diam., bears
S. 79° E., 42 lks. dist., no marks remaining
on burned blaze. (Record, 49 lks.)

A cedar, 37 ins. diam., bears N. 47° W.,
65 lks. dist., with scribe marks T20S R8W
visible on partially healed blaze.

and a bearing tree marked in 1954

A hemlock, 32 ins. diam., bears S. 10° E.,
100 lks. dist., with scribe marks T20S R8W
S19 BT visible on open blaze.

and a new bearing tree

A hemlock, 11 ins. diam., bears N. 89° E.,
67 lks. dist., mkd. T20S R8W S18 BT.

Set a 5 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner reestablished by
Thomas A. Tillman, and Joseph S. Gawron,
in 1954)

The closing corner of secs. 13 and 24, T. 20 S., R. 9 W.,
on the E. bdy. of the Tp., monumented with an iron post,
2 ins. diam., firmly set, projecting 4 ins. above
ground, with brass cap mkd.

| | |
|---------|--------|
| T 20 S | T 20 S |
| CC S 13 | S 18 |
| S 24 | R 8 W |
| R 9 W | |
| 1954 | |

from which bearing trees marked in 1954

A cedar, 25 ins. diam., bears S. 21 3/4° W.,
26 lks. dist., no marks remaining on burned
blaze. Rescribed T20S R9W S24 CC BT on new
blaze.

A fir, 55 ins. diam., bears N. 63° W.,