

County Surveyor's Record, Douglas County, Oregon

18715

Remonumentation of Certain Original Corner Points,
T. 20 S., R 8 W., Willamette Meridian, Oregon

18

CHAINS

iron post.

(Rehabilitating a corner established by
William P. Wright, in 1883, and remonumented
by Thomas A. Tillman, Joseph S. Gawron,
Hans W. Thielsen, and Raymond M. Bicknell,
in 1954)

The cor. of secs. 7 and 18 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 20 S	T 20 S
R 9 W	S 7
S 13	S 18
	R 8 W
	1954

from which the remains of the original bearing trees

A root hole, bears S. 63° E., 30 lks. dist., with a down dogwood alongside, 10 ins. diam., with healed blaze.

A hemlock stump, 18 ins. diam., bears S. 56° W., 5 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, S. 46° W.)

A root hole, bears N. 65° W., 36 lks. dist., with a down maple alongside, 38 ins. diam., with healed blaze.

and a bearing tree marked in 1954

A hemlock, 23 ins. diam., bears N. 84° E., 49 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a new bearing tree

A hemlock, 40 ins. diam., bears S. 39 1/2° E., 110 lks. dist., mkd. T20S R8W S18 BT.

Set a 5 ft. steel fence post alongside the iron post.

North Boundary, T. 20 S., R. 8 W.,
Willamette Meridian, Oregon

(Rehabilitating a corner reestablished by
Marvin J. Lytle and Palmer Norseth,
in 1952)

The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 19 S	R 8 W
S 35	S 36
S 2	S 1
T 20 S	
	1952

from which bearing trees marked in 1952