

County Surveyor's Record, Douglas County, Oregon

16716

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 23 ins. diam., bears N. 57° E., 23 lks. dist., healed blaze. (Record N. 52° E.)

A fir, 15 ins. diam., bears S. 69 1/2° E., 38 lks. dist., healed blaze. (Record 35 lks.)

A fir, 15 ins. diam., bears S. 68 1/4° W., 28 lks. dist., healed blaze.

A fir, 20 ins. diam., bears N. 49 1/2° W., 54 lks. dist., healed blaze.

Set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating corners established by Charles M. Collier, in 1891, and remonumented by Marvin J. Lytle and Palmer Norseth, in 1952)

The 1/4 sec. cor. of secs. 2 and 35, determined at record bearing and distance from the remaining bearing tree marked in 1952:

A burned and dead fir, 19 ins. diam., bears N. 66 3/4° E., 26 lks. dist., with healed blaze.

Locate an iron post, 36 ins. long, 1 in. diam., lying on the ground, at base of the NE. bearing tree, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 35}{S \ 2}$$

1952

At the corner point

Reset the iron post, 28 ins. in the ground from which a new bearing tree

A burned and dead fir, 30 ins. diam., bears N. 57° W., 52 lks. dist., mkd. 1/4 S35 BT.

Set a 6 ft. steel fence post alongside the iron post.

The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

$$\begin{array}{r} T \ 19 \ S \ R \ 8 \ W \\ S \ 34 \ | \ S \ 35 \\ \hline S \ 3 \ | \ S \ 2 \\ T \ 20 \ S \ R \ 8 \ W \\ 1952 \end{array}$$

from which the remaining original bearing tree

A fir, 44 ins. diam., bears S. 85° W., 31 lks. dist., with healed blaze.

and bearing trees marked in 1952

A hemlock, 18 ins. diam., bears N. 37° E., 122 lks. dist., with scribe marks T19S R8W