

County Surveyor's Record, Douglas County, Oregon

16717

Remonumentation of Certain Original Corner Points,
T. 20 S., R 8 W., Willamette Meridian, Oregon

CHAINS

S35 BT visible on open blaze. (Record,
N. 32° E.)

A fir, 60 ins. diam., bears S. 52 1/2° E.,
105 lks. dist., with no marks remaining
on burned blaze. Rescribed T20S R8W S2 BT
on new blaze.

A fir, 38 ins. diam., bears N. 38° W., 53 lks.
dist., with healed blaze. (Record, 50 lks.)

Set a 6 ft. steel fence post alongside the iron
post.

The 1/4 sec. cor. of secs. 3 and 34, monumented with an
iron post, 1 in. diam., firmly set, projecting 12 ins.
above ground, with brass cap mkd.

1/4 $\frac{S\ 34}{S\ 3}$
1952

from which the original bearing trees

A fir, 26 ins. diam., bears N. 10° W.,
29 lks. dist., with healed blaze. (Record,
N. 15° W.)

A fir, 30 ins. diam., bears S. 5° W.,
15 lks. dist., with healed blaze. (Record,
S. 12° W., 13 lks.)

The cor. of secs. 3, 4, 33, and 34, monumented with an
iron post, 2 ins. diam., firmly set, projecting 8 ins.
above ground, with brass cap mkd.

T 19 S R 8 W
 $\frac{S\ 33\ S\ 34}{S\ 4\ S\ 3}$
1952

from which the remaining original bearing trees

A fir, 42 ins. diam., bears N. 26 1/2° E.,
73 lks. dist., with healed blaze.

A fir, 42 ins. diam., bears S. 49° E.,
69 lks. dist., with healed blaze. (Record,
60 lks.)

A fir, 68 ins. diam., bears N. 54° W.,
83 lks. dist., with healed blaze. (Record,
N. 56 3/4° W., 77 lks.)

and the remains of the bearing tree marked in 1952

A sawed hemlock stump, 28 ins. diam., bears
S. 55 3/4° W., 90 lks. dist., with scribe marks
T20S R8W S4 BT visible on open blaze.

Set a 6 ft. steel fence post alongside the iron
post.

Subdivision, T. 20 S., R. 8 W.,
Willamette Meridian, Oregon