

County Surveyor's Record, Douglas County, Oregon

16721

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

remaining on burned blaze. Rescribed 1/4
S23 BT on new blaze.

Set a 6 ft. steel fence post alongside the
iron post.

The cor. of secs. 13, 14, 23, and 24, monumented with an
iron post, 2 ins. diam., firmly set, projecting 12 ins.
above ground, with brass cap mkd.

T 20 S, R 8 W
S 14 | S 13
S 23 | S 24
1954

from which the remains of the bearing trees marked in
1954

A burned fir snag, 27 ins. diam., bears
N. 51° E., 81 lks. dist., with fragmentary
scribe marks visible on partially healed
and burned blaze.

A burned maple snag, 30 ins. diam., bears
S. 45 1/4° E., 83 lks. dist., with scribe
marks T20S R8W S24 BT visible on open and
burned blaze.

A burned maple snag, 37 ins. diam., bears
S 73° W., 22 lks. dist., with scribe marks
BT visible on partially healed and burned
blaze.

A burned maple snag, 25 ins. diam., bears
N. 27° W., 34 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the iron
post.

The 1/4 sec. cor. of secs. 13 and 24, monumented with an
iron post, 1 in. diam., firmly set, projecting 4 ins.
above ground, and in a mound of stone, 1 ft. base, to
top, with brass cap mkd.

1/4 S 13
S 24
1954

from which bearing trees marked in 1954

A cedar, 33 ins. diam., bears N. 66° E.,
76 lks. dist., with fragmentary scribe marks
visible on partially healed and burned blaze.
Rescribed 1/4 S13 BT on new blaze.

A cedar, 28 ins. diam., bears S. 36 1/4° E.,
46 lks. dist., with fragmentary scribe
marks visible on partially healed and
burned blaze. Rescribed 1/4 S24 BT on new
blaze.

The cor. of secs. 11, 12, 13, and 14, monumented with an
iron post, 2 ins. diam., firmly set, projecting 14 ins.
above ground, with brass cap mkd.