

# County Surveyor's Record, Douglas County, Oregon

16723

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 65 ins. diam., bears N. 23° W.,  
48 lks. dist., mkd. 1/4 S12 BT.

(Rehabilitating corners reestablished by  
Thomas A. Tillman, Joseph S. Gawron, Hans W. Thielsen,  
and Raymond M. Bicknell, in 1954)

The 1/4 sec. cor. of secs. 11 and 12, monumented with an  
iron post, 1 in. diam., firmly set, projecting 8 ins.  
above ground, with brass cap mkd.

1/4  
S 11 | S 12  
1954

from which remains of the bearing trees marked in 1954

A burned fir snag, 11 ins. diam., bears  
S. 54 1/4° E., 22 lks. dist., with healed  
blaze. (Record, 47 lks.)

A burned fir snag, 14 ins. diam., bears  
S. 65° W., 47 lks. dist., with healed  
blaze. (Record, S. 63 1/2° W., 22 lks.)

and a new bearing tree

A fir, 26 ins. diam., bears S. 71° E., 62 lks.  
dist., mkd. 1/4 S12 BT.

Set a 6 ft. steel fence post alongside the  
iron post.

The cor. of secs. 1, 2, 11, and 12, monumented with an  
iron post, 2 ins. diam., firmly set, projecting 14 ins.  
above ground, with brass cap mkd.

*FDOK PER ROBERTS  
DEC 1986 M103-63*

T 20 S R 8 W  
S 2 | S 1  
S 11 | S 12  
1954

from which bearing trees marked in 1954

A fir, 12 ins. diam., bears N. 48° E.,  
7 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 52 1/2° E.,  
41 lks. dist., with healed blaze. (Record,  
39 lks.)

A fir, 14 ins. diam., bears S. 20° W.,  
8 lks. dist., with healed blaze.

A fir, 21 ins. diam., bears N. 50° W.,  
41 lks. dist., with healed blaze.

The 1/4 sec. cor. of secs. 1 and 12, monumented with an  
iron post, 1 in. diam., firmly set, projecting 6 ins.  
above ground, and in a mound of stone, 3 ft. base, to  
top, with brass cap mkd.

1/4 S 1  
S 12  
1954