

# County Surveyor's Record, Douglas County, Oregon

16724

Remonumentation of Certain Original Corner Points,  
T. 20 S., R 8 W., Willamette Meridian, Oregon

## CHAINS

from which bearing trees marked in 1954

A fir, 11 ins. diam., bears N. 37° E.,  
21 lks. dist., with healed blaze. Rescribed  
1/4 S1 BT on new blaze.

A fir, 16 ins. diam., bears S. 60 1/4° W.,  
21 lks. dist., with healed blaze. Rescribed  
1/4 S12 BT on new blaze.

The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron  
post, 1 in. diam., firmly set, projecting 12 ins. above  
ground, with brass cap mkd.

FD OK PER ROBERTS  
DEC-86 M 103-63

1/4  
S 2 | S 1  
1954

from which bearing trees marked in 1954

A fir, 14 ins. diam., bears S. 44° E.,  
26 lks. dist., with healed blaze. (Record,  
S. 41 1/2° E.)

A fir, 24 ins. diam., bears S. 78 1/2° W.,  
11 lks. dist., with healed blaze. (Record,  
S. 81 1/2° W.)

(Rehabilitating corners reestablished by  
Thomas A. Tillman, in 1950)

The 1/4 sec. cor. of secs. 34 and 35, monumented with an  
iron post, 1 in. diam., firmly set, projecting 12 ins.  
above ground, with brass cap mkd.

1/4  
S 34 | S 35  
1950

from which the remains of the trees marked in 1950

A burned fir snag, 33 ins. diam., bears  
N. 66° E., 29 lks. dist., with healed blaze.

A burned and dead fir, 26 ins. diam., bears  
N. 46° W., 12 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the  
iron post.

The cor. of secs. 26, 27, 34, and 35, monumented with an  
iron post, 2 ins. diam., firmly set, projecting 10 ins.  
above the ground, with brass cap mkd.

T 20 S R 8 W  
S 27 | S 26  
S 34 | S 35  
1950

from which the remains of the bearing trees marked in  
1950

A burned cedar snag, 47 ins. diam., bears  
N. 70 1/4° E., 37 lks. dist., with scribe  
marks S26 BT visible on partially healed