

County Surveyor's Record, Douglas County, Oregon

16729

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 20 ins. diam., bears S. 31-3/4° E.,
7 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 30° W.,
42 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears N. 68-1/2° W.,
38 lks. dist., with healed blaze.

and new bearing tree

A fir, 20 ins. diam., bears N. 43-1/2° E.,
27 lks. dist., mkd. T20S R8W S11 BT.

The 1/4 sec. cor. of secs. 11 and 14, monumented with an
iron post, 1 in. diam., firmly set, projecting 12 ins.
above ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

1/4 S 11
S 14
1954

from which bearing trees mkd. in 1954

A fir, 15 ins. diam., bears S. 57° W.,
54 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 43 1/2° W.,
17 lks. dist., with healed blaze.

and new bearing trees

A fir, 18 ins. diam., bears N. 34 1/2° E.,
26 lks. dist., mkd. 1/4 S11 BT.

A fir, 10 ins. diam., bears S. 76° E.,
50 lks. dist., mkd. 1/4 S14 BT.

Set a 6 ft. steel fence post alongside the iron
post.

The 1/4 sec. cor. of secs. 10 and 11, monumented with an
iron post, 1 in. diam., firmly set, projecting 3 ins.
above ground, with brass cap mkd.

1/4 S 10 | S 11
1954

from which bearing trees mkd. in 1954

An alder, 14 ins. diam., bears N. 41 1/4° E.,
21 lks. dist., with scribe marks 1 BT
visible on bark. (Record, 23 lks.)

A fir, 34 ins. diam., bears S. 36° W., 54 lks.
dist., with healed blaze. Rescribed 1/4 S10
BT on new blaze.

and a new bearing tree

A fir, 48 ins. diam., bears N. 26° E.,
65 lks. dist., mkd. 1/4 S11 BT.

The cor. of secs. 2, 3, 10, and 11, monumented with an