

County Surveyor's Record, Douglas County, Oregon

16730

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

33

CHAINS

iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 20 S R 8 W
S 3 | S 2
S 10 | S 11
1954

from which the remains of the bearing trees marked in 1954

A dead fir, 36 ins. diam., bears N. 70° E., 30 lks. dist., with healed blaze.

A fir snag, 66 ins. diam., bears S. 45-3/4° E., 29 lks. dist., no marks remaining on burned blaze. Rescribed T20S R8W S11 BT on new blaze.

A fir snag, 36 ins. diam., bears S. 48° W., 22 lks. dist., no marks remaining on burned blaze. Rescribed T20S R8W S10 BT on new blaze.

A fir snag, 46 ins. diam., bears N. 56-3/4° W., 18 lks. dist., no marks remaining on burned blaze. Rescribed T20S R8W S3 BT on new blaze.

The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

1/4 S 2
S 11
1954

from which bearing trees marked in 1954

A fir, 20 ins. diam., bears N. 16° W., 28 lks. dist., with healed blaze.

A fir, 23 ins. diam., bears S. 40-1/4° W., 59 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the iron post.

The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4
S 3 | S 2
1954

from which bearing trees mkd. in 1954

A fir, 19 ins. diam., bears N. 50° E., 15 lks. dist., with healed blaze. (Record, N. 30° E.)

A fir, 23 ins. diam., bears S. 83° W., 10 lks. dist., no marks remaining on burned blaze. (Record, S. 60° W.) Rescribed 1/4 S3 BT on new blaze.