

County Surveyor's Record, Douglas County, Oregon

16731

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

(Rehabilitating corners reestablished by
Thomas A. Tillman, in 1950)

The $\frac{1}{2}$ sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

$\frac{1}{2}$
S 33 | S 34
1950

from which the remains of the bearing trees marked in 1950

A burned fir, 20 ins. diam., bears S. 85° E.,
19 lks. dist., with healed blaze

A burned fir, 16 ins. diam., bears N. 81° W.,
21 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

(Rehabilitating a corner established by
William P. Wright, in 1884, and remonumented
by Thomas A. Tillman, in 1950)

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

T 20 S R 8 W
S 28 | S 27
S 33 | S 34
1950

from which the remains of the bearing trees marked in 1950

A sawed fir stump, 44 ins. diam., bears
S. 61° E., 23 lks. dist., no marks remaining
on burned blaze. Rescribed T20S R8W S34 BT
on new blaze.

A burned madrone snag, 7 ins. diam., bears
S. 17° W., 25 lks. dist., no marks remaining
on burned blaze. (Record, S. 19° W., 27 lks.)

A burned fir stump, 22 ins. diam., bears
N. 21° W., 67 lks. dist., no marks remaining
on burned blaze. Rescribed T20S R8W S28 BT
on new blaze.

and a new bearing tree

A burned cedar stump, 20 ins. diam., bears
N. 47-1/2° E., 50-1/2 lks. dist., mkd. T20S R8W
S27 BT.

(Rehabilitating a corner reestablished by
Thomas A. Tillman, in 1950)

The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.