

County Surveyor's Record, Douglas County, Oregon

16736

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A burned hemlock stump, size indeterminate,
bears N. 44° W., 9 lks. dist., no marks
remaining.

and new bearing trees

A fir stump, 54 ins. diam., bears
S. 72° E., 91 lks. dist., mkd. 1/4 S15 BT.

A hemlock snag, 10 ins. diam., bears
S. 81° W., 33 lks. dist., mkd. 1/4 S16 BT.

Set a 6 ft. steel fence post alongside the iron
post.

(Rehabilitating a corner established by
William P. Wright, in 1884, and remonumented
by Thomas A. Tillman, Joseph S. Gawron,
Hans W. Thielsen, and Raymond M. Bicknell, in 1954)

The cor. of secs. 9, 10, 15, and 16, momimented with an
iron post, 2 ins. diam., firmly set, projecting 8 ins.
above ground, with brass cap mkd.

T	20	S	R	8	W
		S	9	S	10
		S	16	S	15
					1954

from which the remains of the original bearing trees

A burned fir, 50 ins. diam., bears S. 80° W.,
49 lks. dist., no marks visible on burned
blaze. Rescribed T20S R8W S16 BT on new
blaze.

A burned fir, 50 ins. diam., bears N. 36° W.,
35 lks. dist., no marks visible. Rescribed
T20S R8W S9 BT on new blaze.

and the remains of the bearing trees marked in 1954

A burned and dead hemlock, 18 ins. diam.,
bears N. 78° E., 12 lks. dist., no marks
remaining on burned blaze. Rescribed T20S
R8W S10 BT on new blaze.

A burned fir snag, 43 ins. diam., bears
S. 30° E., 44 lks. dist., no marks remaining
on burned blaze. (Record, 47 lks.) Rescribed
T20S R8W S15 BT on new blaze.

A burned hemlock snag, 11 ins. diam., bears
S. 28-1/2° W., 34 lks. dist., no marks remaining
on burned blaze.

(Rehabilitating corners reestablished by
Thomas A. Tillman, Joseph S. Gawron, Hans W. Thielsen,
and Raymond M. Bicknell, in 1954)

The 1/4 sec. cor. of secs. 10 and 15, monumented with an
iron post, 1 in. diam., firmly set, level with the
surface of the ground, with brass cap mkd.