

County Surveyor's Record, Douglas County, Oregon

16739

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 25 ins. diam., bears S. 80° W.,
97 lks. dist., mkd. 1/4 S32 BT.

Set a 5 ft. steel fence post alongside the
iron post.

The cor. of secs. 28, 29, 32, and 33, monumented with an
iron post, 2 ins. diam., firmly set, projecting 8 ins.
above ground, with brass cap mkd.

T 20 S R 8 W
S 29 | S 28
S 32 | S 33
1950

from which the remains of the original bearing trees

A burned fir, 32 ins. diam., bears N. 38° E.,
9 lks. dist., with healed blaze.

A burned fir, 30 ins. diam., bears S. 63° W.,
29 lks. dist., with healed blaze.

and the remains of the bearing trees marked in 1950

A burned fir, 17 ins. diam., bears
S. 65 1/2° E., 37 lks. dist., with healed
blaze. (Record, 35 lks.)

A burned fir, 17 ins. diam., bears
N. 21 1/2° W., 42 lks. dist., with healed
blaze. (Record, 40 lks.)

Set a 5 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner reestablished by
Thomas A. Tillman, in 1950)

The 1/4 sec. cor. of secs. 28 and 29, monumented with an
iron post, 1 in. diam., firmly set, projecting 2 ins.
above ground, with brass cap mkd.

1/4
S 29 | S 28
1950

from which the remains of the bearing tree marked in
1950

A burned fir stump, 9 ins. diam., bears
N. 31° W., 24 lks. dist., no marks remaining.

and a new bearing tree and a reference monument

A burned fir stump, 35 ins. diam., bears
N. 42 1/2° E., 151 lks. dist., mkd. 1/4 S28 BT.

An iron post, 28 ins. long, 2 1/2 ins. diam.,
set 24 ins. in the ground, for a reference
monument, bears N. 41° W., 58 lks. dist.,
with brass cap mkd. 1/4 S29 RM 1967 and an
arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the iron
post