

County Surveyor's Record, Douglas County, Oregon

16743

Remonumentation of Certain Original Corner Points,
T 20 S R 8 W Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 8 W
1/4
S 17 | S 16
1967

from which a new bearing tree

A sawed fir stump, 48 ins. diam., bears S. 42° W., 80 lks. dist., mkd. 1/4 S17 BT.

Set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating corners established by William P. Wright, in 1884, and remonumented by Thomas A. Tillman, Joseph S. Gawron, Hans W. Thielsen, and Raymond M. Bicknell, in 1954)

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 20 S R 8 W
S 8 | S 9
S 17 | S 16
1954

from which the remains of the original bearing trees

A sawed fir stump, 86 ins. diam., bears S. 47° E., 68 lks. dist., no marks remaining on decayed blaze.

A maple, 41 ins. diam., bears S. 61° W., 53 lks. dist., with healed blaze.

A sawed fir stump, 41 ins. diam., bears N. 23° W., 41 lks. dist., with healed blaze.

and the remaining bearing trees marked in 1954

A cedar, 35 ins. diam., bears S. 56 1/4° E., 76 lks. dist., with scribe marks T20S R8W S16 BT visible on open blaze.

A fir, 75 ins. diam., bears S. 85 1/2° W., 48 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A cedar, 26 ins. diam., bears N. 8 1/2° W., 29 lks. dist., with scribe marks T20S R8W S8 BT visible on partially healed blaze.

and a new bearing tree

A cedar, 40 ins. diam., bears N. 31° E., 74 1/2 lks. dist., mkd. T20S R8W S9 BT.

Set a 5 ft. steel fence post alongside the iron post.

The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins.