

County Surveyor's Record, Douglas County, Oregon

16746

Remonumentation of Certain Original Corner Points,
T. 20 S. R. 8 W. Willamette Meridian, Oregon

CHAINS

N. 21 1/4° W., 47 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

(Rehabilitating corners reestablished by
Thomas A. Tillman, in 1950)

The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4 $\frac{S\ 30}{S\ 31}$
1950

from which the remains of the bearing trees marked in 1950

A sawed fir stump, 60 ins. diam., bears N. 53 3/4° W., 12 lks. dist., with healed blaze.

A burned fir, 50 ins. diam., bears S. 53 3/4° E., 21 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

1/4
S 30 | S 29
1950

from which the remains of the bearing trees marked in 1950

A hemlock snag, 11 ins. diam., bears East, 13 lks. dist., no marks remaining on burned blaze.

A fir snag, 63 ins. diam., bears S. 78° W., 25 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

(Rehabilitating a corner established by
William P. Wright, in 1884, and remonumented
by Thomas A. Tillman, in 1950)

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 20 S R 8 W
S 19 | S 20
S 30 | S 29
1950