

# County Surveyor's Record, Douglas County, Oregon

16751

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees marked in 1954

A fir, 21 ins. diam., bears N. 32 lks.  
dist., with healed blaze.

A fir, 33 ins. diam., bears S. 35° E.,  
47 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the  
iron post.

---

The 1/4 sec. cor. of secs. 7 and 18, monumented with an  
iron post, 1 in. diam., firmly set, projecting 8 ins.  
above ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 7 \\ S 18 \end{array}$$

1954

from which bearing trees marked in 1954

A hemlock, 16 ins. diam., bears N. 15° E.,  
29 lks. dist., with healed blaze.

A hemlock, 22 ins. diam., bears S. 60 1/4° E.,  
38 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron  
post.

An electronic survey control point, ABC 9, established  
during the Aerial Electronic Cadastral Resurvey in the  
Oxbow Ridge Fire Area, in 1967, located in the southeast  
quarter of section 16, on the highest point on a ridge  
separated by North and South Sister Creeks. This point  
is monumented with an iron post, 28 ins. long, 2 1/2 ins.  
diam., 26 ins. in the ground, with brass cap mkd.

A B C 9

---

1967

from which

A sawed fir stump, 29 ins. diam., bears  
N. 98° E., 30 lks. dist., mkd. ABC 9 BT.

A hemlock snag, 12 ins. diam., bears S. 27° E.,  
68 lks. dist., mkd. ABC 9 BT.