

County Surveyor's Record, Douglas County, Oregon

16755

Corrective Dependent Resurvey,
Portion of Subdivisional Lines,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- A hemlock, 12 ins. diam., bears N. 19 1/4° W.,
5 1/2 lks. dist., mkd. N 1/16 S11 BT.
- Destroy the marks on the 1971 bearing trees.
- Descend 150 ft. over N. slope.
- 25.30 Creek, 2 lks. wide, course W.; asc. 70 ft. over S. slope.
- 29.00 Spur, slopes W.; desc. 450 ft. over N. slope.
- 41.20 Dirt road, 25 lks. wide, bears N. 40° E. and S. 40° W.
- 41.90 The closing cor. of secs. 11 and 12, on the S. bdy. of
sec. 2, perpetuated and recorded by Vernon R. Tracy,
Deputy County Surveyor, in 1968, monumented with an iron
post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S
CC

S 11 | S 12
R 8 W
1968

from which remains of the original bearing trees

A fir snag, 26 ins. diam., bears S. 74° E., 43 lks.
dist., with fragmentary scribe marks visible on
bark blaze.

A sawed hemlock stump, 15 ins. diam., bears
S. 63° W., 29 lks. dist., with scribe marks
T26S R8W S11 visible on opened blaze.

and a bearing tree mkd. by Tracy

A hemlock, 16 ins. diam., bears S. 46° E., 46 lks.
dist., with healed blaze.

and a bearing tree mkd. by Peterson and Berry

A hemlock, 13 ins. diam., bears S. 36 1/2° W., 86 lks.
dist., with fragmentary scribe marks visible on
partially healed blaze.

From this point the cor. of secs. 1 and 2 only, bears
N. 89° 23' E., 2.29 chs. dist., perpetuated and recorded
by Vernon R. Tracy, Deputy County Surveyor, in 1968,
monumented with an iron post, 1 1/2 ins. diam., firmly set,
projecting 8 ins. above ground, with brass cap mkd.

T 26 S
S 2 | S 1

R 8 W
1968

from which the remains of the original bearing trees

A root hole, bears N. 60° E., 58 lks. dist.