

# County Surveyor's Record, Douglas County, Oregon

16763

Dependent Resurvey, Portion, E. Bdy.,  
Tps. 32 S., Rs. 4 and 5 W., Willamette Mer., Oregon

**CHAINS**

N. 0°04' E., on the E. bdy. of sec. 36, marking and blazing the true line.

Descend 14 ft. over N. slope, through moderate timber and undergrowth, across partially logged area.

1.61 From this point, the original closing cor. of secs. 25 and 36, T. 32 S., R. 5 W., bears West, 0.04 chs. dist., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1964, monumented with a galvanized iron pipe, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R	T32S	R
5	S25	4
W	S36	W
CC		
1964		

from which the remains of the original bearing trees  
A sawed and decayed fir stump, 40 ins. diam., bears S. 11 W., 73½ lks. dist., no marks remaining. (record, S. 10°W., 70 lks.)

A roothole, bears N. 23°W., 53 lks. dist., alongside of which is lying a burned and decayed yew, 10 ins. diam., no marks remaining. (Record, N. 24°W., 55 lks.)

and a bearing tree mkd. by G. J. Wenderoth, Registered Land Surveyor, No. 5, in 1956

A fir, 16 ins. diam., bears N. 36½°W. 60 lks. dist., with healed blaze.

and a bearing tree mkd. by Godfrey

A white fir, 9 ins. diam., bears S. 71½°W., 21 lks. dist., with healed blaze.

Thence, on the E. bdy. of sec. 25.

Descend 25 ft. over N. slope.

4.50 Bull Run Creek, 15 lks. wide, course S. 60°W., asc. 165 ft. over S. slope.

6.30 Gravelled road, 30 lks. wide, bears E. and W., also enter rock quarry, edge bears E. and W.

8.75 Leave rock quarry, edge bears E. and W.

12.47 True point for the closing cor. of secs. 30 and 31, T. 32 S., R. 4 W., hereinafter described.

This point is located on spur, slopes S. 5°W., asc. slightly along spur.

14.40 Leave spur, desc. 40 ft. over NW slope.

20.70 Bottom of descent, slopes SW, asc. 240 ft. over S. slope.

26.20 Dirt road, 15 lks. wide, bears NE and SW.