

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion, E. Bdy.,
Tps. 32 S., Rs. 4 and 5 W., Willamette Mer., Oregon

16764

CHAINS

40.38

Point for the $\frac{1}{4}$ sec. cor. of sec. 25 only, at proportionate dist., there is no remaining evidence of the original cor.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S
 $\frac{1}{4}$ S 25
R 5 W
1979

from which

A fir, 36 ins. diam., bears N. $83\frac{1}{2}^{\circ}$ W., 123 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

A fir, 10 ins. diam., bears N. 7° W., $37\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Ascend 135 ft. over SE. slope.

45.40

Spur, slopes SE., asc. 85 ft. over SE. slope.

52.47

Point for the $\frac{1}{4}$ sec. cor. of sec. 30 only, T. 32 S., R. 4 W., at midpoint on the W. bdy. of sec. 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S
 $\frac{1}{4}$ S 30
R 4 W
1979

from which

A fir, 34 ins. diam., bears N. 29° E., 52 lks. dist. mkd. $\frac{1}{4}$ S30 BT.

A fir, 20 ins. diam., bears S. 47° E., $81\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S30 BT.

Ascend 200 ft. over SE slope.

57.50

Dirt road, 15 lks. wide, bears NE and SW.

62.60

Divide between Bull Run Creek and Starvout Creek, bears NE. and SE., also gravelled road, 20 lks. wide, bears N. 25° W. and S. 30° W., in curve, desc. 45 ft, over NE slope.

67.40

Bottom of descent, slopes E., asc. 70 ft. over SE. slope.

72.47

Point for the N $\frac{1}{16}$ sec. cor. of sec. 30 only, T. 32 S., R. 4 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to solid rock, and in a mound of stone 3 ft. base, to top, with brass cap mkd.

N $\frac{1}{16}$
S 30
1979

from which