

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion, E. Bdy.,
Tps, 32 S., Rs. 4 and 5 W., Willamette Mer., Oregon

16766

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, cedar, madrone, oak, maple, alder,
yew, and chinquapin; undergrowth, vine maple, poison oak,
Oregon grape, dogwood, salal, fern. and young timber.

N. $0^{\circ}38'$ E., on the E. bdy. of sec. 24.

Descend 20 ft. along W. slope, through heavy timber and
dense undergrowth.

10.70 Spur, slopes NW.; desc. 60 ft. over NE. slope.

11.83 Point for the closing cor. of secs. 19 and 30, T. 32 S.,
R. 4 W., at proportionate dist.; there is no remaining
evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in
the ground, with brass cap mkd.

| | |
|--------|-------|
| T 32 S | |
| R 5 W | R 4 W |
| S 24 | S 19 |
| | S 30 |
| | CC |
| | 1979 |

from which

A fir, 18 ins. diam., bears N. 36° E., 94 lks.
dist., mkd. T32S R4W S 19 CC BT.

A fir, 6 ins. diam., bears S. 61° E., $46\frac{1}{2}$ lks.
dist., mkd. T32S R4W S30 CC BT.

Descend 770 ft. over NW. slope.

26.10 Gravelled road, 25 lks. wide, bears N. 20° E. and
S. 20° W.

39.23 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, determined at record
bearing and dist. from the remains of the original
bearing trees

A roothole, bears S 35° E., 8 lks. dist.,
with a down fir alongside, 36 ins. diam.,
with healed blaze.

A roothole, bears S. 73° W., 43 lks. dist.,
with a down fir alongside, 48 ins. diam.,
with scribe marks $\frac{1}{4}$ S BT visible on opened
double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in
the ground, with brass cap mkd.

| | |
|--------|---------------|
| T 32 S | |
| R 5 W | R 4 W |
| S 24 | S 19 |
| | $\frac{1}{4}$ |
| | 1979 |

from which new bearing trees

A fir, 12 ins. diam., bears N. 70° E., 41 lks.
dist., mkd. $\frac{1}{4}$ S19 BT.