

County Surveyor's Record, Douglas County, Oregon

16767

Dependent Resurvey, Portion, E. Bdy.,
Tps. 32 S., Rs. 4 and 5 W., Willamette Mer., Oregon

CHAINS

A fir, 7 ins. diam., bears N. 61° W., 59 lks.
dist., mkd. ½ S24 BT.

N. 0° 24' E., beginning new measurement.

Descend 150 ft. over NW slope.

4.40 Creek, 2 lks. wide, course N. 10° E.; desc. 255 ft. along
broken slope changing to NE slope.

23.20 Same creek, 6 lks. wide, course N. 40° W.; asc. 10 ft.
over SW slope.

25.90 Creek, 3 lks. wide, course W.; asc. 35 ft. along W.
slope.

40.05 The cor. of secs. 13, 18, 19. and 24. perpetuated and
recorded by George J. Wenderoth, Registered Land Surveyor
No. 5, in 1945, monumented with an iron rod, 1 in. diam.,
firmly set, projecting 6 ins. above ground, from which
the remains of an original bearing tree:

A decayed fir stump, 20 ins. diam., bears S. 45 W.,
34 lks. dist., with no marks remaining.

and bearing trees mkd. by Wenderoth

A fir, 16 ins. diam., bears S. 23 ¾° E., 20 lks. dist.,
with healed double blaze.

A chinquapin, 9 ins. diam., bears S. 44 ¾° W., 38 lks.
dist. with scribe marks S24 visible on partially healed double blaze.

A chinquapin, 9 ins. diam., bears N. 55° W., 12 ½
lks. dist., with scribe marks BT visible on par-
tially healed double blaze.

and a bearing tree mkd. by R.L. Templin, Jr., Registered
Engineer, No. 3024, in 1956

A fir, 13 ins. diam., bears N. 9° W., 13 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in
the ground, directly over the iron rod, with brass cap
mkd.

| | | | |
|--------|-------|--|--|
| T 32 S | | | |
| R 5 W | R 4 W | | |
| S 13 | S 18 | | |
| S 24 | S 19 | | |
| 1979 | | | |

from which a new bearing tree

A fir, 14 ins. diam., bears N. 67½° E., 15½ lks.
dist., mkd. T32 S R4W S18 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, chinquapin, madrone, yew, maple,
alder, and cedar; undergrowth, vine maple, dogwood,
poison oak, Oregon grape, salal, ceanothus, huckleberry,
hazel, fern, and young timber.