

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of
the Subdivisional Lines, T. 32 S., R. 4 W.,
Willamette Meridian, Oregon

16768

CHAINS

(Restoring the survey by W.S. Chapman and C.S. Nicklin, U.S. Deputy Surveyors, in 1897, and the remonumentation by Hans Thielsen, Cadastral Surveyor, in 1959)

From the cor. of secs. 29,30,31,and 32, perpetuated and recorded by J.M. Powell, Deputy County Surveyor, in 1970, monumented with an iron pipe, 1½ ins, diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 32 S
S 30 | S 29
S 31 | S 32
R 4 W
1970

from which the remains of the original bearing trees

A fir, 54 ins. diam., bears N. 15°E., 49 lks. dist., with healed blaze.

A fir, 29 ins diam., bears S. 26½°W., 111 lks. dist., with healed blaze. (Record, 115 lks.)

A sawed fir stump, 37 ins. diam., bears N. 68½° W., 76 lks. dist., with scribe marks 2S W visible on opened and burned blaze.

and bearing trees mkd. by Powell

A fir snag, 7 ins. diam., bears S. 42° E., 37 lks. dist., with scribe marks T32S R4W S32 CS BT visible on partially healed blaze.

A sugar pine, 17 ins. diam., bears N. 74 1/4° W., 36 1/2 lks. dist., with scribe marks 4W CS B visible on partially healed blaze.

and a new bearing tree

A fir, 20 ins. diam., bears S. 88° E., 76 1/2 lks. dist., mkd. T32S R4W S32 BT.

S. 89° 52' W., bet. secs. 30 and 31, marking and blazing the true line.

Descend 235 ft. over SW. slope, through scattering timber and dense undergrowth.

12.50 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.

13.90 Ravine, drains S. 50° W.; asc. 5 ft. over SE. slope.

14.90 Spur, slopes S. 20° W.; desc. 25 ft. over NW. slope.

19.30 Ravine, drains S. 10° W.; asc. 20 ft. over E. slope.

19.95 Point for the E. 1/16 sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.

E 1/16 $\frac{S\ 30}{S\ 31}$
1979