

County Surveyor's Record, Douglas County, Oregon

16770

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

True point for the closing cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S
R 5 W R 4 W
S 25 | S 30
 | S 31 CC
1979

from which

A fir, 12 ins. diam., bears N. 13 1/2° E., 63 1/2 lks. dist., mkd. T32S R4W S30 CC BT:

A fir, 6 ins. diam., bears S. 24 1/2° E., 6 1/4 lks. dist., mkd. T32S R4W S31 CC BT.

From this point, the original closing cor. of secs. 30 and 31, bears N. 89° 47' W., 0.18 chs. dist., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1964, monumented with a galvanized iron pipe, 1 in. diam., firmly set, projecting 13 ins. above ground with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 32 S
R | S 30 R
5 | S 31 4
W CC W
1964

from which the remains of the original bearing trees

A burned and rotted fir stump, 12 ins. diam., bears N. 48° E., 20 lks. dist., with scribe marks S R4W visible on portion of burned blaze.

A madrone, 13 ins. diam., bears S. 62° E., 37 lks. dist., with decayed blaze.

and bearing trees mkd. by Godfrey

A madrone, 13 ins. diam., bears N. 7 1/4° E., 25 lks. dist., with scribe marks T32S R4W S30 CC BT visible on partially healed blaze.

A fir, 6 ins. diam., bears S. 73° E., 20 1/2 lks. dist., with healed double blaze.

A live oak, 18 ins. diam., bears S. 8° W., 30 1/4 lks. dist., with illegible scribe marks visible on partially healed double blaze.

From this same point, the angle point bet. secs. 31 and 36 bears S. 0° 04' W, 12.47 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, hemlock, oak, chinquapin, madrone, and yew; undergrowth, vine maple, hazel, poison oak, salal, huckleberry, Oregon grape, fern, and young timber.

From the cor. of secs. 29, 30, 31, and 32.